

Technical Data Sheet

DT0424/00

POLYURETHANE THINNER FOR GLOSS LACQUERS

Supersedes previous issue dated 10/16/00

DATE 12/14/16

Technical characteristics:

Specific gravity (kg/l):	0.845 ± 0.030
Flash point:	+17 °C
Drying speed (max 100 – min 0):	40
Resistivity (Mohm per cm at 20°C):	50
Shelf-life:	If the product is properly stored, shelf-life is unlimited.

General characteristics

DT0424/00 is a polyurethane thinner very well balanced for diluting gloss lacquers.

It improves wetting, reduces overspray and the formation of pinholes and has proved as particularly suitable during summer.

It can be used as it is or mixed with DT0441/00 in case a slower drying is required.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.