

COMPANY WITH
MANAGEMENT SYSTEM
- UNI EN ISO 9001 - UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18 tel. +39 051 770 511 - fax +39 051 777 437 www.sayerlack.com Cod. Fisc. e Reg. Impr. Bo 08866930152 P. IVA: IT 00494251200 - R.E.A. n. 313180 Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

## Technical Data Sheet

## AH1503/00 HARDENER FOR WATERBORNE COATINGS

DATE 02/22/12

Area of use	2-pack waterborne polyurethane coatings

## **Technical characteristics**

Solids content (%)	70 ± 1
Specific gravity (kg/l):	1.170 ± 0.050
Shelf-life (months):	12

## **General characteristics**

AH1503/00 is a polyurethane hardener expressly designed for 0 gloss effect 2-pack waterborne polyurethane coatings.

It can be added to part A and dispersed manually; however, dispersion obtained by means of mechanical stirrers, ensures optimal and consistent results.

As far as technical characteristics such as percentage of use, pot-life, etc., are concerned, please refer to the technical data sheet of part A.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.