

Technical Data Sheet

TH_CATALIZZATORI PER POLIURETANICI_IT TH_HARDENERS FOR POLYURETHANES_EN

Annula e sostituisce / Supersedes previous 16 January 2018

DATA / DATE 23 January 2018

IT: Le caratteristiche qualitative ed i consigli d'uso sono riportati nelle schede tecniche dei componenti A. I catalizzatori isocianici sono sensibili all'umidità; le confezioni vanno stoccate in ambiente asciutto e devono rimanere ermeticamente chiuse. Quando viene aperta la confezione il prodotto deve essere utilizzato in giornata.

EN: As to other characteristics and method of use, please refer to the technical data sheets relating to part A. Isocyanate hardeners are affected by humidity, therefore packages shall be hermetically sealed and kept dry. Once the package has been opened, the product shall be used up within the same day.

CODE	SHELF-LIFE SCADENZA	SOLID CONTENT RESIDUO SECCO	SPECIFIC GRAVITY PESO SPECIFICO
CODICE	(months) (mesi)	%	Kg/l
TH0146/00	24	25 ± 1	0,986 ± 0,030
TH0222/00	24	24 ± 1	0,965 ± 0,030
TH0333/00	24	24 ± 1	0,965 ± 0,030
TH0613/00	24	21 ± 1	0,930 ± 0,030
TH0620/00	24	26 ± 1	0,955 ± 0,030
TH0675/00	24	28 ± 1	0,950 ± 0,030
TH0703/00	24	24 ± 1	0,955 ± 0,030
TH0711/00	24	28 ± 1	0,940 ± 0,030
TH0712/00	24	23 ± 1	0,960 ± 0,030
TH0713/00	24	22 ± 1	0,930 ± 0,030
TH0715/00	24	34 ± 1	0,970 ± 0,030
TH0718/00	24	28 ± 1	0,940 ± 0,030
TH0720/00	24	26 ± 1	0,955 ± 0,030
TH0721/00	24	44 ± 1	1,000 ± 0,030
TH0722/00	24	29 ± 1	0,969 ± 0,030
TH0723/00	24	21 ± 1	0,914 ± 0,030
TH0724/00	24	31 ± 1	0,950 ± 0,030
TH0727/00	24	32 ± 1	0,967 ± 0,030
TH0728/00	24	30 ± 1	0,980 ± 0,030
TH0733/00	24	49 ± 1	1,015 ± 0,030
TH0735/00	24	44 ± 1	0,998 ± 0,030
TH0738/00	24	39 ± 1	1,000 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

COMPANY WITH
MANAGEMENT SYSTEM
- UNI EN ISO 9001 -
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
Cod. Fisc. e Reg. Impr. Bo 08866930152
P. IVA: IT 00494251200 - R.E.A. n. 313180
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

CODE	SHELF-LIFE SCADENZA	SOLID CONTENT RESIDUO SECCO	SPECIFIC GRAVITY PESO SPECIFICO
CODICE	(months) (mesi)	%	Kg/l
TH0744/00	24	49 ± 1	1,060 ± 0,030
TH0746/00	24	37 ± 1	1,020 ± 0,030
TH0748/00	24	28 ± 1	0,950 ± 0,030
TH0749/00	24	32 ± 1	0,950 ± 0,030
TH0755/00	24	27 ± 1	0,970 ± 0,030
TH0756/00	6	75 ± 3	1,170 ± 0,030
TH0759/00	24	24 ± 1	0,930 ± 0,030
TH0760/00	24	42 ± 1	1,012 ± 0,030
TH0761/00	24	50 ± 1	1,070 ± 0,030
TH0765/00	24	35 ± 1	0,982 ± 0,030
TH0767/00	24	23 ± 1	0,950 ± 0,030
TH0773/00	24	28 ± 1	0,940 ± 0,030
TH0775/00	24	28 ± 1	0,950 ± 0,030
TH0779/00	24	27 ± 1	0,970 ± 0,030
TH0780/00	24	28 ± 1	0,960 ± 0,030
TH0781/00	24	70 ± 2	1,150 ± 0,030
TH0784/00	24	29 ± 1	0,960 ± 0,030
TH0787/00	24	28 ± 1	0,950 ± 0,030
TH0788/00	24	34 ± 1	1,000 ± 0,030
TH0790/00	24	36 ± 1	0,950 ± 0,030
TH0793/00	24	25 ± 1	0,934 ± 0,030
TH0799/00	24	28 ± 1	0,948 ± 0,030
TH0801/00	24	24 ± 1	0,940 ± 0,030
TH0805/00	24	24 ± 1	0,940 ± 0,030
TH0808/00	24	24 ± 1	0,940 ± 0,030
TH0825/00	24	40 ± 1	0,980 ± 0,030
TH0908/00	24	80 ± 1	1,100 ± 0,030
TH0925/00	24	26 ± 1	0,960 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.

COMPANY WITH
MANAGEMENT SYSTEM
- UNI EN ISO 9001 -
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
Via del Fiffò, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
Cod. Fisc. e Reg. Impr. Bo 08866930152
P. IVA: IT 00494251200 - R.E.A. n. 313180
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

CODE	SHELF-LIFE SCADENZA	SOLID CONTENT RESIDUO SECCO	SPECIFIC GRAVITY PESO SPECIFICO
CODICE	(months) (mesi)	%	Kg/l
TH1400/00	24	50 ± 1	1,059 ± 0,030
TH2513/00	24	31 ± 1	0,965 ± 0,030
TH2520/00	24	34 ± 1	0,940 ± 0,030
TH2526/00	24	27 ± 1	0,940 ± 0,030
TH2530/00	12	75 ± 1	1,070 ± 0,030
TH2533/00	24	27 ± 1	0,965 ± 0,030
TH2537/00	24	29 ± 1	1,020 ± 0,030
TH2569/00	24	18 ± 1	0,950 ± 0,030
TH2580/00	24	20 ± 1	1,001 ± 0,030
TH2587/00	24	20 ± 1	1,000 ± 0,030
TH3192/00	24	31 ± 1	0,990 ± 0,010
TH6367/00	24	24 ± 1	0,940 ± 0,030
TH7918/00	24	25 ± 1	0,940 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.