

COMPANY WITH
MANAGEMENT SYSTEM
- UNI EN ISO 9001 -
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
Cod. Fisc. e Reg. Impr. Bo 08866930152
P. IVA: IT 00494251200 - R.E.A. n. 313180
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

Technical Data Sheet

THX HARDENERS FOR POLYURETHANES

Supersedes previous issue dated 04.03.17

DATE 04/14/17

CODE	SHELF-LIFE (months)	SOLIDS CONTENT (%)	SPECIFIC GRAVITY
TH0613/00	24	21 ± 1	0,930 ± 0,030
TH0620/00	24	26 ± 1	0,960 ± 0,030
TH0675/00	24	28 ± 1	0,950 ± 0,030
TH0703/00	24	24 ± 1	0,960 ± 0,030
TH0712/00	24	23 ± 1	0,960 ± 0,030
TH0749/00	24	32 ± 1	0,950 ± 0,030
TH6367/00	24	28 ± 1	0,950 ± 0,030
THL3073/00	24	27 ± 1	0,930 ± 0,030
THL3163/00	24	35 ± 1	0,980 ± 0,030
THL7111/00	24	36 ± 1	0,970 ± 0,030
THL7112/00	24	27 ± 1	0,920 ± 0,030
THL7170/00	24	30 ± 1	0,980 ± 0,030
THL7988/00	24	50 ± 1	1,010 ± 0,030
THV6332/00	24	37 ± 1	0,980 ± 0,030
THV7624/00	24	48 ± 1	0,990 ± 0,030
THV7764/00	24	43 ± 1	0,960 ± 0,030
THL3256/00	12	38 ± 1	0,970 ± 0,030
THL3109/00	24	40 ± 1	0,975 ± 0,030
THL3354/00	24	50 ± 1	1,001 ± 0,030
THL3364/00	24	24 ± 1	0,940 ± 0,030
SC2536/00	24	25 ± 1	0,960 ± 0,030
THL3355/00	12	19 ± 1	0,880 ± 0,030
THL3626/00	24	19 ± 1	0,894 ± 0,030
THL3625/00	24	23 ± 1	0,960 ± 0,030
THL3627/00	24	36 ± 1	0,950 ± 0,030
THL3348/00	12	28 ± 1	0,950 ± 0,030
THL3508/00	24	32 ± 1	0,966 ± 0,030

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.

WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.